



## Towed Bellow Sprayer

**Turbo bellow sprayer for spraying orchards for disease and pest control.**

- A towed turbo sprayer with a stainless steel tank in varying size at the client's discretion.
- Varied bellow options in various diameters adapted to various crops.
- Adjustment of the bellow size by a professional representative of Degania Sprayers when typifying the product with the farmer.
- Bellow options 1060-913-815mm. Installed in the trailer's rear.
- The bellow has reinforced plastic wings with an option to change their angle, a unique feature allowing for the machine's adjustment to the tractor's size and/or changing the bellow's exhaust air speed.
- The turbo bellow requires less power from the tractor and produces less noise.
- Options for a piston or a diaphragm pump, at the client's discretion.
- The tank is equipped with a mechanical or hydraulic stirrer.
- Two spraying arcs, each with 28 sprinklers operated by a valve switchboard located close to the operator.
- An option for 2 additional half-arches positions at the farmer's discretion.
- Each sprinkler has a valve permitting adjustment and control.



## Technical Specifications

<b>Control</b>	Mechanical/Electrical/ Computerized
<b>Number of Sprinklers</b>	28+28 optional
<b>Number of Arches</b>	2 primary + 2 short
<b>Type of Sprinklers</b>	80-degree Cone
<b>Shaft</b>	3-point
<b>Tank Size</b>	1000-3000 liters
<b>Tank Material</b>	Stainless Steel
<b>Bellow</b>	815 – 913 – 1060
<b>Air Speed</b>	40-45 m/s
<b>Air cubic meters per hour</b>	Per manufacturer catalogue
<b>Pump</b>	PA 154, C120
<b>Pump Type</b>	Centrifugal / Pistons
<b>Tire Size</b>	800mm
<b>Tire Width</b>	300mm